

Wedgegard® Type CFS Flexible Coupling

Torque Table / in-lbs



DATASHEET Version 7/2020

Model	CFS 500-160		CFS 500-198		CFS 700-220		CFS 700 - 275		CFS 950 - 350		CFS 1000 - 425	
WEDGEPIN	W37		W37		W50		W50		W100		W100	
BRASS= B STEEL = S	B	S	B	S	B	S	B	S	B	S	B	S
TORQUE CODES	* Wedgepins x 3		* Wedgepins x 3		* Wedgepins x 3		* Wedgepins x 4		* Wedgepins x 4		* Wedgepins x 4	
O	1375	1896	1375	1896	1375	1896	1375	1896	-	-	-	-
OW	1910	2619	1910	2619	1910	2619	1910	2619	-	-	-	-
GD	2576	3545	2576	3545	2576	3545	2576	3545	-	-	-	-
W	3574	4906	3574	4906	3574	4906	3574	4906	23979	32915	-	146701
WY	5152	7076	5152	7076	5152	7076	5152	7076	33643	46221	-	218336
Y	6801	9334	6801	9334	6801	9334	6801	9334	42635	58546	-	293763
YB	9015	12387	9015	12387	9015	12387	9015	12387	58098	79780	-	368919
BN	9334	-	9334	-	9334	-	9334	-	-	-	-	-
B	10622	14587	10622	14587	10622	14587	10622	14587	69583	95551	-	415728
BG	12387	17003	12387	17003	12387	17003	12387	17003	82189	112863	-	491200
G	15296	20997	15296	20997	15296	20997	15296	20997	103114	141632	-	587166
RG	18494	25411	18494	25411	18494	25411	18494	25411	121014	165274	-	-
R	20809	28580	20809	28580	20809	28580	20809	28580	138915	190794	-	676224
RK	-	-	-	-	-	-	-	-	-	-	-	-
K	-	-	-	-	-	-	-	-	161157	221300	-	716082


* Full complement or single pin can be used.

Torque figures are for full complement of Wedgepins fitted – adjust torques by reducing the number of Wedgepins or fitting multiple code.

Ordering new Wedgepins
Example: W37 - B - R

W37 Wedgepin size	B Material Brass	R Breaking Torque Code Letter
-----------------------------	----------------------------	---

Identification on existing Wedgepin



Tel: +44 (0)1453 750814
Fax: +44 (0)1453 765320
www.howdon.co.uk
sales@howdon.co.uk

