

Wedgegard® Type DFS Flexible Coupling

DATASHEET Version 4/2020

Torque Table / Nm



Model	DFS 350-145		DFS 500-195		DFS 700-240		DFS 950-320		DFS 1000-470		DFS 1200-510		DFS 1400-560		DFS 1600-630	
WEDGE PIN	W37		W37		W50		W75		W100		W100		W120		W120	
Brass = B / STEEL = S	B	S	B	S	B	S	B	S	B	S	B	S	B	S	B	S
TORQUE CODES	* Wedgepins x 3		* Wedgepins x 3		* Wedgepins x 3		* Wedgepins x 3		* Wedgepins x 4		* Wedgepins x 4		* Wedgepins x 4		* Wedgepins x 4	
O	45	62	52	71	126	173	-	-	-	-	-	-	-	-	-	-
OW	62	85	72	99	191	274	-	-	-	-	-	-	-	-	-	-
GD	84	115	97	134	-	-	-	-	-	-	-	-	-	-	-	-
W	116	159	135	185	275	377	830	1140	-	3470	-	3980	-	0	-	0
WY	167	230	194	266	373	512	1165	1600	-	5160	-	5920	-	0	-	0
Y	221	303	256	352	487	705	1475	2030	-	6940	-	7970	-	12240	-	15300
YB	293	402	340	467	712	978	2010	2760	-	8720	-	10000	-	0	-	0
BN	303	-	352	-	-	-	-	-	-	-	-	-	-	-	-	-
B	345	474	400	549	978	1344	2400	3300	-	9820	-	11280	-	17630	-	22040
BG	402	552	467	640	1222	1678	2850	3900	-	11610	-	13330	-	0	-	0
G	497	682	576	791	1494	2050	3600	4900	-	13880	-	15930	-	20240	-	25300
RG	601	825	697	957	1886	2589	4200	5700	-	-	-	-	-	-	-	-
R	676	928	784	1076	1950	2678	4800	6600	-	15980	-	18350	-	25000	-	31240
RK	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
K	-	-	-	-	2032	2791	5600	7650	-	16920	-	19430	-	31340	-	39180

* Full complement or single pin can be used.


Torque figures are for single Wedgepin fitted – adjust torques by adding Wedgepins or fitting multiple codes.

Ordering new Wedgepins

Example: W37 - B - R

W37 Wedgepin size	B Material Brass	R Breaking Torque Code Letter
-----------------------------	----------------------------	---

Identification on existing Wedgepin



Tel: +44 (0)1453 750814
 Fax: +44 (0)1453 765320
www.howdon.co.uk
sales@howdon.co.uk

