

# Wedgegard® Type DFS Flexible Coupling

## Torque Table / ft-lbs



DATASHEET Version 4/2020

Model	DFS 350-145		DFS 500-195		DFS 700-240		DFS 950-320		DFS 1000-470		DFS 1200-510		DFS 1400-560		DFS 1600-630	
WEDGE PIN	W37		W37		W50		W75		W100		W100		W120		W120	
Brass = B / STEEL = S	B	S	B	S	B	S	B	S	B	S	B	S	B	S	B	S
TORQUE CODES	* Wedgepins x 3		* Wedgepins x 3		* Wedgepins x 3		* Wedgepins x 3		* Wedgepins x 4		* Wedgepins x 4		* Wedgepins x 4		* Wedgepins x 4	
O	33	45	38	52	93	128	-	-	-	-	-	-	-	-	-	-
OW	46	63	53	73	141	202	-	-	-	-	-	-	-	-	-	-
GD	62	85	72	99	-	-	-	-	-	-	-	-	-	-	-	-
W	86	118	100	136	203	278	612	841	-	2559	-	2935	-	-	-	-
WY	123	170	143	196	275	378	859	1180	-	3806	-	4366	-	-	-	-
Y	163	224	189	260	359	520	1088	1497	-	5119	-	5878	-	9028	-	11285
YB	216	297	251	344	525	722	1482	2036	-	6432	-	7376	-	-	-	-
BN	223	-	260	-	-	-	-	-	-	-	-	-	-	-	-	-
B	254	349	295	405	722	991	1770	2434	-	7243	-	8320	-	13003	-	16256
BG	297	407	344	472	901	1238	2102	2876	-	8563	-	9832	-	-	-	-
G	366	503	425	583	1102	1512	2655	3614	-	10237	-	11749	-	14928	-	18660
RG	443	609	514	706	1391	1910	3098	4204	-	-	-	-	-	-	-	-
R	498	685	578	794	1438	1975	3540	4868	-	11786	-	13534	-	18439	-	23041
RK	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
K	-	-	-	-	1499	2058	4130	5642	-	12480	-	14331	-	23115	-	28898

\* Full complement or single pin can be used.


Torque figures are for single Wedgepin fitted – adjust torques by adding Wedgepins or fitting multiple codes.

Ordering new Wedgepins

Example: W37 - B - R

<b>W37</b> Wedgepin size	<b>B</b> Material Brass	<b>R</b> Breaking Torque Code Letter
-----------------------------	----------------------------	---

Identification on existing Wedgepin



Tel: +44 (0)1453 750814  
 Fax: +44 (0)1453 765320  
[www.howdon.co.uk](http://www.howdon.co.uk)  
[sales@howdon.co.uk](mailto:sales@howdon.co.uk)

